

Appl. No. 10/807,164
Amdt. Dated December 3, 2004
Reply to Office action of November 10, 2004

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Original) A bicycle having at least a portion of control cable internally routed comprising:
 - a frame, said frame including a head tube;
 - a handlebar stem received and supported in said head tube, said handlebar stem having an internal passageway therethrough;
 - a handlebar secured to said handlebar stem;
 - a control lever secured to said handlebar; and
 - a control cable attached to said control lever and extending from said control lever through said passageway in said handlebar stem and attached to a control mechanism.
2. (Original) The bicycle of claim 1 wherein the control cable further extends through the head tube and exits from the bottom of the head tube.
3. (Original) The bicycle of claim 1 further comprising a fork yoke passing through the head tube and having an internal passageway wherein the handlebar stem is received and supported in the head tube by being received and supported in the fork yoke, the internal passageway of the handlebar stem opens into the internal passageway of the

Appl. No. 10/807,164
Amdt. Dated December 3, 2004
Reply to Office action of November 10, 2004

fork yoke and the control cable passes through the passageways of both the handlebar stem and the fork yoke.

4. (Original) The bicycle of claim 3 further comprising a collar for connecting the handlebar stem to the fork yoke without closing the internal passageways of the handlebar stem or fork yoke.

5. (Original) The bicycle of claim 1 wherein the internal passageway of the handlebar stem extends from the head tube to a point forward of where the handlebar is secured to the handlebar stem and the handlebar is secured to the handlebar stem without closing the internal passageway of the handlebar stem.

6. (Original) The bicycle of claim 1 wherein the handlebar stem has a first end received and supported in the head tube and a second end and the handlebar stem is bent such that the second end points forward at an angle greater than 45 degrees from the first end.

7. (Original) The bicycle of claim 6 wherein the internal passageway of the handlebar stem extends through the bent portion of the handlebar stem.

8. (Original) The bicycle of claim 1 having a connection between the handlebar and the handlebar stem that permits the handlebar to be secured to the handlebar stem in a range of positions along the length of the handlebar stem.

Appl. No. 10/807,164
Amdt. Dated December 3, 2004
Reply to Office action of November 10, 2004

9. (Original) The bicycle of claim 8 wherein the handlebar has a collar for securing the handlebar to the handlebar stem without closing the internal passageway of the handlebar stem.

10. (Original) The bicycle of claim 1 wherein the handlebar stem is received and supported in the head tube at an adjustable depth of insertion.

11. (Original) The bicycle of claim 1 wherein the control cable, after passing through the handlebar stem, passes into the frame and extends through a portion of the frame.

12. (Original) The bicycle of claim 1 wherein the handlebar, handlebar stem and control cable are covered by a casing.

13. (Original) A set of parts for use as in a headset for a bicycle comprising,
- a) a fork having a fork yoke;
 - b) a handlebar stem adapted to be inserted into a first end of the fork yoke;
 - c) a connector adapted to be placed around the outside of a portion of the fork yoke and handlebar stem and connect the fork yoke to the handlebar stem.

Appl. No. 10/807,164
Amdt. Dated December 3, 2004
Reply to Office action of November 10, 2004

14. (Original) The set of parts of claim 13 wherein the connector comprises a collar adapted to compress the fork yoke and handlebar stem so as to create a frictional connection between them.

15. (Original) The set of parts of claim 14 wherein the fork yoke has one or more longitudinal slits in the first end.

16. (Original) The set of parts of claim 14 wherein the first end of the fork yoke and the collar are threaded such that the collar may be threaded onto the first end of the fork yoke.

17. (Original) The set of parts of claim 14 wherein the collar has an abutment adapted to compress a bearing assembly of the headset.

18. (Currently Amended) A~~The~~ set of parts for a bicycle comprising of claim 13 wherein,
a) a the handlebar stem having has a first end and a second end, the first end adapted
to be connected to a fork assembly of the bicycle inserted into the first end of the fork
yoke, and further comprising

b)d) a handlebar; and,

e)e) a second connector adapted to attach the handlebar to the handlebar
stem with the second connector located within a range of positions
between the ends of the handlebar stem wherein the handlebar and
second connector do not cover the second end of the handlebar stem.

Appl. No. 10/807,164
Amdt. Dated December 3, 2004
Reply to Office action of November 10, 2004

19. (Currently Amended) The set of parts of claim 18 wherein the second connector includes a collar attached to the handlebar and adapted to grasp the outside of the handlebar stem.

20. (Currently Amended) The set of parts of claim ~~19~~ 18 wherein the handlebar stem is bent such that the second end of the handlebar stem points forward at an angle greater than 45 degrees from the first end of the handlebar stem.

21. (Currently Amended) The set of parts of claim 18 wherein the handlebar stem has an internal passageway extending between the first end of the handlebar stem and the second end of the handlebar stem.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☒ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.